



INTERNAL DRIVER				
A	PER ESTERNO	M 1	F 2	CODE
76	114	2 3/8 AR	2 3/8 AR	TRI078MFR238R238114W
	127	2 3/8 AR	2 3/8 AR	TRI078MFR238R238127W
	133	2 3/8 AR	2 3/8 AR	TRI078MFR238R238133W
	140	2 3/8 AR	2 3/8 AR	TRI078MFR238R238140W
90	140	2 3/8 AR	2 3/8 AR	TRI090MFR238R238140W
	152	2 3/8 AR	2 3/8 AR	TRI090MFR238R238152W
	168	2 3/8 AR	2 3/8 AR	TRI090MFR238R238168W
114	168	3 1/2 AR	3 1/2 AR	TRI114FMR312R312168W
	178	3 1/2 AR	3 1/2 AR	TRI114FMR312R312178W
	194	3 1/2 AR	3 1/2 AR	TRI115FMR312R312194W
	203	3 1/2 AR	3 1/2 AR	TRI114FMR312R312203W
	220	3 1/2 AR	3 1/2 AR	TRI114FMR312R312220W
	244	3 1/2 AR	3 1/2 AR	TRI114FMR312R312244W
	254	3 1/2 AR	3 1/2 AR	TRI114FMR312R312254W
	273	3 1/2 AR	3 1/2 AR	TRI114FMR312R312273W
127	300	3 1/2 AR	3 1/2 AR	TRI114FMR312R312300W
	194	3 1/2 IF	3 1/2 IF	TRI127MFF312F312194W
	203	3 1/2 IF	3 1/2 IF	TRI127MFF312F312203W
	220	3 1/2 IF	3 1/2 IF	TRI127MFF312F312220W
	244	3 1/2 IF	3 1/2 IF	TRI127MFF312F312244W
	254	3 1/2 IF	3 1/2 IF	TRI127MFF312F312254W
	274	3 1/2 IF	3 1/2 IF	TRI127MFF312F312274W
300	3 1/2 IF	3 1/2 IF	TRI127MFF312F312300W	
140	203	4 1/2 AR	4 1/2 AR	TRI140FMR412R412203W
	220	4 1/2 AR	3 1/2 AR	TRI140FMR412R312220W
	220	4 1/2 AR	4 1/2 AR	TRI140FMR412R412220W
	244	4 1/2 AR	4 1/2 AR	TRI140MFR412R412244W
	254	4 1/2 AR	4 1/2 AR	TRI140MFR412R412254W
	273	4 1/2 AR	4 1/2 AR	TRI140MFR412R412273W